

DATA SHEET

Version: 1 June 2017



GERA EDS Shuttering angles

Applications To block screed floor surfaces at steps or in door areas.

Properties Lining highly resistant to wet screed.
Straight-edged design for precise blocking.

Technical data

Material: Raw materials: recycled cardboard (from former drinks packaging)
Lined with aluminium and PE

Delivery:

Dimensions	80 x 40 x 3 mm	Length 1.80 m
	60 x 60 x 3 mm	Length 1.80 m
	50 x 40 x 3 mm	Length 1.80 m

1 bundle	=	25 shuttering angles
1 pallet	=	750 shuttering angles

Notes: We recommend all of the components in the GERA EDS (screed insulation system) range to ensure perfect screed insulation:

- GERA EDS Shuttering angles
- GERA EDS Expansion joint profile
- GERA EDS Corner profile
- GERA EDS Edge insulation strips
- GERA EDS Impact sound insulation sheeting
- GERA EDS Verbind und Dicht (Fit and seal)
- GERA EDS Frame profile

The above values are intended as a guide or have been obtained under laboratory conditions and do not constitute any guarantee of product properties. We recommend carrying out preliminary tests to check that our products are suitable for use with other products. Under our General Terms and Conditions, we guarantee consistently high product quality, but due to the many possible applications we cannot accept any liability for specific results in practical applications. This data sheet supersedes any previous versions.

GERA Chemie GmbH, Elbestr. 31-33, 45478 Mülheim an der Ruhr, Germany
T: +49 208 802080, F: +49 208 801810, info@gera-chemie.de, www.gera-chemie.de