

DATA SHEET

Version: 1 June 2017



EUROFIBER

Screed fibres in 1-kg bags

Applications

Polypropylene fibres to reduce cracking. Specially formulated for use in screeds, concretes and mortars, for sprayed concrete and precast concrete elements.

Properties

EUROFIBER has been specially developed for use in screeds, concretes, mortars, sprayed concrete and precast concrete elements to minimise cracking as much as possible, particularly during the early setting stage. Shrinkage and stress cracks appearing before the screed has completely set can often lead to later complaints, even if these cracks are usually only a visual defect.

Technical data

Material:

EUROFIBER is a technical polypropylene fibre with a broad range of applications. It possesses excellent mechanical and physical properties, and is also alkali-resistant. The fibre, which is supplied in 1-kg bags, is approx. 19 mm long.

Addition:

Approx. 140 g of EUROFIBER per 200 litres of screed mix

How much to use:

Rule of thumb: 10 g of Eurofiber per sqm and per cm height of the screed

Instructions for use:

Add the dissolving bag to the screed mix as early as possible to ensure even fibre distribution. The fibres are also distributed more evenly in the screed mix if the paper bag is torn slightly.

Packaging unit:

Every PE bag contains 1 kg
Every box contains 13 PE bags
Every pallet holds 18 boxes

The above values are intended as a guide or have been obtained under laboratory conditions and do not constitute any guarantee of product properties. We recommend carrying out preliminary tests to check that our products are suitable for use with other products. Under our General Terms and Conditions, we guarantee consistently high product quality, but due to the many possible applications we cannot accept any liability for specific results in practical applications. This data sheet supersedes any previous versions.