

DATA SHEET

Version: 1 June 2017



GERA Universal

Screed admixture for cement screed

Applications GERA Universal is suitable for the preparation of bonded and floating cement-based screed.

Properties GERA Universal is a liquid admixture used in the preparation of cement-bound screed. Plasticising improves workability and the compressive strength and bending tensile strength of the screed are increased. Given the improved early strength characteristics in particular, the screed will accept cautious foot traffic after just 24-48 hours, depending on the temperature.

Technical data

Application: GERA Universal is added to the mixing water

Addition: 1% of cement weight = 0.5 kg GERA Universal for 50 kg of cement

How much to use: 1 kg of GERA Universal is enough for approximately 6-7 m² of screed

Storage: GERA Universal freezes below -1°C.
Thaw frozen admixture at room temperature.

Delivery: 10 kg cans / 60 cans per pallet. / Colouring and customised labelling available.

Notes: GERA Universal can be coloured as required.
Can also be delivered with customised labels.

The above values are intended as a guide or have been obtained under laboratory conditions and do not constitute any guarantee of product properties. We recommend carrying out preliminary tests to check that our products are suitable for use with other products. Under our General Terms and Conditions, we guarantee consistently high product quality, but due to the many possible applications we cannot accept any liability for specific results in practical applications. This data sheet supersedes any previous versions.

GERA Chemie GmbH, Elbestr. 31-33, 45478 Mülheim an der Ruhr, Germany
T: +49 208 802080, F: +49 208 801810, info@gera-chemie.de, www.gera-chemie.de