

# DATA SHEET

Version: 1 June 2017



## GERA Adhesive Tape Alu 80

made from pure aluminium

### Applications

Connections and bonding of protective materials in:  
Cellar and wet room protection  
Cold storage insulation, cold room  
Sauna  
Roof insulation  
Ventilation ducts, air-conditioning ducts.

### Properties

GERA Adhesive Tape Alu 80 is moisture-resistant with a high level of durability and shear strength, even at fluctuating temperatures. It is highly resistant to mechanical stress with excellent adhesion/initial adhesion.

### Technical data

Material:	Adhesive tape made from pure aluminium 99.5 and synthetic rubber adhesive
DIN standards:	Of low flammability pursuant to DIN 4102 B1
Finished weight:	Approx. 250 g/m <sup>2</sup>
Elongation at break:	5%
Breaking force:	30 N/cm
Adhesion to steel:	9.0 N/cm
Temperature range:	-40°C to +80°C
Construction material class:	DIN 4102 B1
Water vapour permeability:	> 1 g/m <sup>2</sup> /d = practically impermeable to water vapour
Storage:	Store in a dry place, protected from sunlight
Delivery:	Thickness: Approx. 80 µm (pursuant to DIN 53105-T01-77) Width: Approx. 50 mm (standard, other widths available) Length: Approx. 100 m (standard, short rolls available)
Notes:	Avoid damage through mechanical fixings.  GERA adhesive tape Alu 80 does not contain harmful substances. Dispose of small amounts of waste as residual waste and in accordance with local regulations.

The above values are intended as a guide or have been obtained under laboratory conditions and do not constitute any guarantee of product properties. We recommend carrying out preliminary tests to check that our products are suitable for use with other products. Under our General Terms and Conditions, we guarantee consistently high product quality, but due to the many possible applications we cannot accept any liability for specific results in practical applications. This data sheet supersedes any previous versions.